

120x120x38 mm

93.0~138.0 CFM



■ Specifications

	Bearing	Rating Voltage	Power Current	Power Consumption	Speed	Air Flow	Static Pressure	Noise	Weight	Curve
	• VAPO	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H ₂ O)	(dB(A))	(g)	
MEC0381V1-0000-A99	•	12	833	10.0	3100	138.0	0.36	48.0	218.0	1
MEC0381V2-0000-A99	•	12	421	5.1	2600	116.0	0.26	44.0	218.0	2
MEC0381V3-0000-A99	•	12	241	2.9	2100	93.0	0.18	37.0	218.0	3
MEC0382V1-0000-A99	•	24	383	9.2	3100	138.0	0.36	48.0	218.0	1
MEC0382V2-0000-A99	•	24	224	5.4	2600	116.0	0.26	44.0	218.0	2
MEC0382V3-0000-A99	•	24	130	3.1	2100	93.0	0.18	37.0	218.0	3
MEC0384V1-0000-A99	•	48	203	9.7	3100	138.0	0.36	48.0	218.0	1
MEC0384V2-0000-A99	•	48	120	5.8	2600	116.0	0.26	44.0	218.0	2
MEC0384V3-0000-A99	•	48	69	3.3	2100	93.0	0.18	37.0	218.0	3

Model	Bearing	Rating Voltage	Power Current	Power Consumption	Speed	Air Flow	Static Pressure	Noise	Weight	Curve
	• 2BALL Sleeve	(VDC)	(mA)	(WATTS)	(RPM)	(CFM)	(inch-H ₂ O)	(dB(A))	(g)	
EEC0381B1-0000-A99	•	12	833	10.0	3100	138.0	0.36	48.0	214.0	1
EEC0381B2-0000-A99	•	12	421	5.1	2600	116.0	0.26	44.0	214.0	2
EEC0381B3-0000-A99	•	12	241	2.9	2100	93.0	0.18	37.0	214.0	3
EEC0382B1-0000-A99	•	24	383	9.2	3100	138.0	0.36	48.0	214.0	1
EEC0382B2-0000-A99	•	24	224	5.4	2600	116.0	0.26	44.0	214.0	2
EEC0382B3-0000-A99	•	24	130	3.1	2100	93.0	0.18	37.0	214.0	3
EEC0384B1-0000-A99	•	48	203	9.7	3100	138.0	0.36	48.0	214.0	1
EEC0384B2-0000-A99	•	48	120	5.8	2600	116.0	0.26	44.0	214.0	2
EEC0384B3-0000-A99	•	48	69	3.3	2100	93.0	0.18	37.0	214.0	3

■ Air Flow-Static Pressure Characteristics

■ External dimensions(mm)