

MULTÍMETRO DIGITAL LCR



Technical data

Basic Function	Range	9808
DC Voltage	200mV/2V/20V/200V	±(0.5%+3)
	1000V	±(0.8%+10)
AC Voltage	200mV	±(0.8%+5)
	2V/20V/200V	±(0.8%+5)
	750V	±(1.2%+10)
DC Current	200uA/2mA/20mA	±(0.8%+10)
	200mA	±(0.8%+10)
	20A	±(2.0%+5)
AC Current	200uA/2mA/20mA	±(0.8%+10)
	200mA	±(0.8%+10)
	20A	±(2.0%+5)
Resistance	200Ω	±(0.8%+5)
	2kΩ/20kΩ/200kΩ/2MΩ	±(0.8%+3)
	20MΩ	±(1.0%+25)
Inductance	200MΩ	±(5.0%+30)
	2mH/20mH/200mH/2H/20H	±(2.5%+30)
Capacitance		
	200uF/2000uF	±(5.0%+10)
Frequency	20nF/200nF/2uF/20uF	±(3.5%+20)
Celsius	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/10MHz	±(1.0%+3)
Fahrenheit	(-20~1000)°C	±(1.0%+5)
	(0~1832)°F	±(0.75%+5)
Special Function		
Diode/Transistor		✓
Continuity Buzzer		✓
Low battery indication		✓
Hold		Peak Hold
Auto power off		✓
Backlight		✓
Function protection		✓
200mA protection		✓
Input impedance		10MΩ
Sampling rate		3 times/s
AC frequency response		40-1000Hz
Operation way		Manual range
Max. Display		1999
LCD Size		70*50mm
Battery		9V(6F22)